

TrackCore Operating Room, the industry leading tissue and implant management software, integrates with intelligent RFID-enabled enclosures to automate your chain of custody and inventory management without human intervention.

AUTOMATE CHAIN OF
CUSTODY TRACKING

IMPROVE REGULATORY
COMPLIANCE

ABSOLUTE
ACCOUNTABILITY

INVENTORY
OPTIMIZATION



HOW RFID TECHNOLOGY WORKS

ONE

Place the internet-enabled RFID enclosure at the point of use.

TWO

Pre-authorized users are able to access the enclosure with RFID-enabled badges.

THREE

Users can then add or remove RFID-tagged inventory from the enclosure.

FOUR

The user, items added or removed, date/time, and temperature are all automatically tracked.

W trackcoreinc.com P 616.632.2222 E sales@trackcoreinc.com

CONFIDENTIAL: This document is intended only for the original recipient. The information contained herein is confidential and may constitute inside or non-public information under international, federal, or state securities laws. Unauthorized forwarding, printing, copying, distribution or use of such information is strictly prohibited and may be unlawful. Please contact TrackCore, Inc. at +1.616.632.2222.



TC-132 | Small RFID Cabinet | 7.9 ft³ Intelligent Cabinet

DETAILS AND DIMENSIONS

| COMPONENT | SPECIFICATION |
|---------------------|--|
| External Dimensions | 44"H x 24"W x 24"D |
| Internal Dimensions | 33"H x 23"W x 18"D (for each side) |
| External Space | 44"H x 24"W x 48"D Place 3" from back wall and allow a minimum 21" for door clearance |
| Optional Riser | 23" H x 22" W x 24" D |
| Volume | 7.9 ft ³ |
| Weight | 200 lbs |
| Security Device | Strike Latch lock |
| Environmental | RoHS Compliant |



| COMMUNICATION | SPECIFICATION | POWER | SPECIFICATION |
|------------------|-----------------------------|-------------------|--------------------------------|
| RFID Frequencies | 902 to 928 MHz | Electrical Power | 120 VAC, 60 Hz, 1 A |
| Communications | Ethernet, optional cellular | Plug Types | NEMA 5-15 |
| Access Control | LF pass reader | Power Consumption | 84 W max |
| | | Battery Backup | 24VDC, 1.3 Ah sealed lead acid |

W trackcoreinc.com
P 616.632.2222
 E sales@trackcoreinc.com

CONFIDENTIAL: This document is intended only for the original recipient. The information contained herein is confidential and may constitute inside or non-public information under international, federal, or state securities laws. Unauthorized forwarding, printing, copying, distribution or use of such information is strictly prohibited and may be unlawful. Please contact TrackCore, Inc. at +1.616.632.2222.

