

Automated Inventory ManagementUltra Low Temp RFID Freezer: TC-188

TrackCore Operating Room, the industry leading tissue and implant management software, integrates with intelligent RFID-enabled enclosures to automate your chain of custody and inventory management without human intervention.

AUTOMATE CHAIN OF CUSTODY TRACKING

IMPROVE REGULATORY COMPLIANCE

ABSOLUTE ACCOUNTABILITY

INVENTORY OPTIMIZATION



HOW RFID TECHNOLOGY WORKS

ONE

Place the internet-enabled RFID enclosure at the point of use.

TWO

Pre-authorized users are able to access the enclosure with RFID-enabled badges.

THREE

Users can then add or remove RFID-tagged inventory from the enclosure.

FOUR

The user, items added or removed, date/time, and temperature are all automatically tracked.



trackcoreinc.com



616.632.2222



sales@trackcoreinc.com

CONFIDENTIAL: This document is intended only for the original recipient. The information contained herein is confidential and may constitute inside or non-public information under international, federal, or state securities laws. Unauthorized forwarding, printing, copying, distribution or use of such information is strictly prohibited and may be unlawful. Please contact TrackCore, Inc. at +1.616.632.2222.



TC-188 | Ultra Low Temp RFID Freezer | 14.9 ft³ Intelligent Freezer

DETAILS AND DIMENSIONS

| COMPONENT | SPECIFICATION | |
|---------------------|---|--|
| External Dimensions | 78"H x 23"W x 38.5"D Place 6" from back wall | |
| Internal Dimensions | 51.2"H x 17.8"W x 28.3"D | |
| Volume | 14.9 ft' | |
| Weight | 622 lbs | |
| Temperature Range | - 86° C to - 50° C | |
| Security Device | Electronic Door Lock | |
| Access Control | LF pass reader | |
| Refrigerant | R - 134a non-CFC | |
| Cooling Method | 2-stage cascade system | |
| Defrost Type | Manual | |



| COMMUNICATION | SPECIFICATION | POWER | SPECIFICATION |
|-----------------------------------|--------------------|---------------------|--|
| RFID Frequencies | 902 to 928 MHz | Electrical Power | 115 VAC, 60 Hz, 13 A |
| Communications Ethernet, optional | Ethernet, optional | | 230 VAC, 60 Hz, 13 A |
| | cellular | Plug Type | If 115VAC, then NEMA 5-2 If 230 VAC, then NEMA 6- Dedicated circuit required |
| | Power Consumption | 10.5 kWh/day | |
| | | RFID Battery Backup | 24VDC, 1.3 Ah sealed lead acid |



trackcoreinc.com



P 616.632.2222



E sales@trackcoreinc.com